



Patents
Serial Number: 09/759,579
Group Art Unit: 3635

ATTACHMENT B
CLAIM AMENDMENTS - CLEAN VERSION

COPY OF PAPERS
ORIGINALLY FILED

1. (Once Amended) A brickmoulding for use on the perimeter of windows and doors for receiving siding, comprising:

61 a solid rectangular portion comprising a width, a length, said length being greater than said width, and a thickness, said rectangular portion further comprising a bottom surface and a top surface, said bottom surface for overlying a building structure;

a flange portion carried in approximately parallel relationship by said bottom surface of said rectangular portion, said flange portion extending beyond said width of said rectangular portion; and,

a channel for receiving siding, said channel being formed between said flange portion and said top surface.

62 3. (Once Amended) The brickmoulding of claim 1 wherein said channel further comprises therewithin a step portion adjacent the bottom of said channel, whereby the channel so formed is adapted to cooperatively receive either of two differing thicknesses of siding.

12. (Once Amended) A fenestration for receiving siding in association with an architectural structure, comprising:

a fenestration frame;

a brickmoulding affixed to said fenestration frame for receiving siding, comprising:

3
a rectangular portion comprising a width, a length, said length being greater than said width, and a thickness, said rectangular portion further comprising a bottom surface and a top surface, said bottom surface for overlying a building structure;

a flange portion carried in approximately parallel relationship by said bottom surface of said rectangular portion, said flange portion extending beyond said width of said rectangular portion; and,

a channel for receiving siding, said channel being formed between said flange portion and said top surface;

said channel further comprising therewithin a step portion adjacent the bottom of said channel, whereby the channel so formed is adapted to cooperatively receive either of two differing thicknesses of siding.

14. [Cancelled without prejudice]

19
20. (Once Amended) A brickmoulding for use on the perimeter of windows and doors for receiving siding, comprising: a rectangular portion comprising a width, a length, said length being greater than said width, and a thickness, said rectangular portion further comprising a bottom surface and a top surface, said bottom surface for overlying a building structure, said top surface optionally further comprising a decorative portion extending from and carried by said top surface; a flange portion carried in approximately parallel relationship by said bottom surface of said rectangular portion, said flange portion extending beyond said width of said rectangular portion; and, a channel for receiving siding, said channel being formed between said flange portion and said top surface, said channel further comprising therewithin a step portion adjacent the bottom of said channel, whereby the channel so formed is adapted to cooperatively receive either of two differing thicknesses of siding.